



# 9415i (Gen 1)

#### 9410L + Safety = 9415i

# Everything that's great about the 9410L LED Lantern, plus safety certificates

At just 1.4kg (3 pounds) and 392 lumens, the 9415i LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 392 meters. And it's loaded with innovative technology and features you have come to expect from Pelican.

Safety certified for the most volatile work areas, the 9415i LED Lantern is safe and one of the most compact, high output lanterns on the market.

- Built Pelican tough
- Handy push button on/off switch
- High/Low/Flashing Modes
- · Super bright LED beam
- Carrying Strap included



#### **DIMENSIONS**

**Length** 8.75" (22.2 cm)

#### **MATERIALS**

**Body** Anti-static Impact Modified PC/PBT

**O-Ring** EPDM

LensAnti-static coated Polycarbonate (PC)ShroudAnti-static Impact Modified PC/PBT

#### **COLORS**

High Visibility Yellow

#### LIGHT SPECS

Lamp Type LED

#### **POWER**

Battery Size C
Battery Type NiMH
Battery Quantity 4
Batteries Included yes
Rechargeable yes
Charge Time 15 hrs
Battery Level Indicator RGB LED
Volts 4.8v

# WEIGHT

Weight With Batteries 58.2 oz (1650 gr)
Weight Without 0.0 oz (0 gr)
Batteries

www.delga.com



# **SWITCH**

**Switch Type Light Modes**  Push Button

High / Low / Flashing

# **CERTIFICATIONS**

**IECEx** ia ATEX Zone 0

# OTHER

Minimum Pack **Package Code** 

1

В

FL1 STANDARD	HIGH	LOW
314	392 LUMENS	144 LUMENS
	4h 30mins	11h 0mins
	392m	234m
	32767cd	13747cd
	IPX4	

# **ACCESSORIES**



9416 Deck/Dash Charger Base Unit



6057F 110V Transformer (USA)



**6061F**Direct Wiring Rig for Fast
Charger



8056F 12v Plug-in for Fast Charger



9418Z0 Replacement Battery



#### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>

Document created on 12-21-20

