



Model SLM100 shown with mounting base options (ordered separately)



► Model SLM100

StreamLine® Modular Multifunctional LED Beacon

Model SLM100 offers a multifunctional LED beacon with high optical performance. Developed with a multiple input technology, Model SLM100 allows three separate light effects (steady, flashing or rotating) controllable via independent electric contacts.

The steady light option offers a conspicuous and consistent light signal. The flashing mode consists of a triple-flash strobe effect ideal for all applications where an immediate attention gain is mandatory. The rotating light offers a traditional rotating beacon effect without moving parts, which enhances product life.

Model SLM100 body material is a self extinguishing polycarbonate material with high impact and UV resistance suitable for outdoor applications.

FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC*
- PLC compatible with PNP or NPN connections*
- Three separate inputs: steady, flashing or rotating
- 50,000 hour LED
- Five lamp/lens colors: Amber, Blue, Clear, Green and Red
- Seven mounting base options
- Type 4X, IP66 enclosure
- IP69K** compliant
- CE Certified
- UL and cUL listed

* Voltage and PLC connections are dependent on selected base

**IP69K with select bases SLMBS, SLMBD, SLMBP and SLM-RR accessory

MODEL	VOLTAGE	FLASH RATE/MINUTE	ROTATIONS PER MINUTE
SLM100 *	12-24VAC/DC or 120-240VAC	85 (+/-10)	140 (+/-10)

* Indicates color: (A) Amber, (B) Blue, (C) Clear, (G) Green or (R) Red

MAXIMUM OPERATING CURRENT (mA)					
12VDC	24VDC	12VAC	24VAC	120VAC	240VAC
300	150	510	360	100	70


Weight (unit(s) + base = total weight)

SLM100	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT	2-STACK DOCK BASE	3-STACK DOCK BASE
7.05 oz	12-24VAC/DC	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17 oz 0.26 kg	14.46 oz 0.41 kg	21.16 oz 0.60 kg
0.20 kg	120-240 VAC	—	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35 kg	16.58 oz 0.47 kg	24.69 oz 0.70 kg

StreamLine® Modular Multifunctional LED Beacon (SLM100)

SPECIFICATIONS

Lamp Life: 50,000 Hours
 Light Source: LED
 Operating Temperature: -22°F to 122°F -30°C to 50°C



HOW TO ORDER

- Specify model number SLM100 and color
- Specify required mounting base (see chart)
- Optional dome guard
 For shallow mounting base (SLMDG3)
 For deep mounting base (SLMDG4)
- Accessories for Twin and Wall Mount Bases
 Cable Gland, M20, Gray, 2 Pack (K77700416)
 Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
 1" NPT Adapter (SLMNPT1)
 1/2" NPT Adapter (SLMNPT2)
- Accessories for Dock Base
 Wall Mount Bracket (SLMB23W)
 1/2" NPT Adaptor (SLMB23N)
 Retaining Ring (SLM-RR)
 Light Visor (SLMB23V)

MOUNTING BASE OPTIONS

Mounting Base	Model Number	Base Color	Voltage	Dimensions
Shallow Base	SLMBS-012-024GY	Gray	12-24VAC/DC	
	SLMBS-012-024R	Red	12-24VAC/DC	
Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
	SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBD-012-024R	Red	12-24VAC/DC	
	SLMBD-120-240GY	Gray	120-240VAC	
Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
	SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBW-120-240GY	Gray	120-240VAC	
Pipe Mount	SLMBP-012-024GY	Gray	12-24VAC/DC	
	SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBP-120-240GY	Gray	120-240VAC	
Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
	SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBT-120-240GY	Gray	120-240VAC	
2-Stack Dock Base	SLMB2-024GY	Gray	24VAC/DC	
	SLMB2-120-240GY	Gray	120-240VAC	
	SLMB3-024GY	Gray	24VAC/DC	
	SLMB3-120-240GY	Gray	120-240VAC	
Note: Dock bases allow one function per position and include visors.				

