



► Model SLM700

# StreamLine® Modular Electronic Sounder

Model SLM700 is a multifunctional electronic sounder developed with a multiple input technology that is capable of producing two different tones controllable via independent electric contacts.

Model SLM700 offers a high acoustic performance through 2 channels offering 64 tones, 32 tones per input selectable via DIP switch.

Model SLM700 body material is a self-extinguishing polycarbonate material with high impact and UV resistance suitable for outdoor applications.

## FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC\*
- PLC compatible with PNP or NPN connections\*
- Produces two tones
- Choice of 64 selectable tones
- Adjustable volume between 55 dBa to 95 dBa @10' (65-105 dBa @ 1m)

- Seven mounting base options
- Type 3R, IP65 enclosure
- CE Certified
- UL and cUL listed

\*Voltage and PLC connections are dependent on selected base.

| MODEL           | VOLTAGE                   | DECIBELS<br>MIN. - MAX. |        | MAXIMUM OPERATING CURRENT (mA) |          |        |        |
|-----------------|---------------------------|-------------------------|--------|--------------------------------|----------|--------|--------|
|                 |                           | 10'                     | 1M     | 12VAC/DC                       | 24VAC/DC | 120VAC | 240VAC |
| <b>SLM700 *</b> | 12-24VAC/DC or 120-240VAC | 55-95                   | 65-105 | 240                            | 280      | 60     | 35     |

\*For body color, indicate GY for Gray or R for Red.

### Weight (unit(s) + base = total weight)


| SLM700             | VOLTAGE     | SHALLOW<br>BASE    | DEEP<br>BASE       | WALL<br>MOUNT      | PIPE<br>MOUNT      | TWIN<br>WALL<br>MOUNT | 2-STACK<br>DOCK<br>BASE | 3-STACK<br>DOCK<br>BASE |
|--------------------|-------------|--------------------|--------------------|--------------------|--------------------|-----------------------|-------------------------|-------------------------|
| 7.76 oz<br>0.22 kg | 12-24VAC/DC | 2.12 oz<br>0.06 kg | 4.23 oz<br>0.12 kg | 6.70 oz<br>0.19 kg | 5.29 oz<br>0.15 kg | 9.17 oz<br>0.26 kg    | 14.46 oz<br>0.41 kg     | 21.16 oz<br>0.60 kg     |
|                    | 120-240 VAC | –                  | 6.0 oz<br>0.17 kg  | 8.47 oz<br>0.24 kg | 6.70 oz<br>0.19 kg | 12.35 oz<br>0.35 kg   | 16.58 oz<br>0.47 kg     | 24.69 oz<br>0.70 kg     |



# StreamLine® Modular Electronic Sounder (SLM700)

## SPECIFICATIONS

Operating Temperature: -22°F to 122°F -30°C to 50°C
















ACCESSORIES FOR DOCK BASE

## HOW TO ORDER

- Specify model number:  
SLM700GY - Gray body  
SLM700R - Red body
- Specify required mounting base (see chart)
- Optional dome guard  
For shallow mounting base (SLMDG1)  
For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases  
Cable Gland, M20, Gray, 2 Pack (K77700416)  
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base  
1" NPT Adapter (SLMNPT1)  
1/2" NPT Adapter (SLMNPT2)
- Accessories for Dock Base  
Wall Mount Bracket (SLMB23W)  
1/2" NPT Adaptor (SLMB23N)  
Retaining Ring (SLM-RR)  
Light Visor (SLMB23V)

## MOUNTING BASE OPTIONS

|  | Model Number        | Base Color | Voltage     |  |
|--|---------------------|------------|-------------|--|
| <br>Shallow Base   | SLMBS-012-024GY     | Gray       | 12-24VAC/DC |    |
|  | SLMBS-012-024R      | Red        | 12-24VAC/DC |  |
| <br>Deep Base   | SLMBD-012-024GY     | Gray       | 12-24VAC/DC |   |
|  | SLMBD-PNP-012-024GY | Gray       | 12-24VAC/DC |  |
|  | SLMBD-012-024R      | Red        | 12-24VAC/DC |  |
|  | SLMBD-120-240GY     | Gray       | 120-240VAC  |  |
| <br>Wall Mount  | SLMBW-012-024GY     | Gray       | 12-24VAC/DC |   |
|  | SLMBW-PNP-012-024GY | Gray       | 12-24VAC/DC |  |
|  | SLMBW-120-240GY     | Gray       | 120-240VAC  |  |
| <br>Pipe Mount  | SLMBP-012-024GY     | Gray       | 12-24VAC/DC | Pipe Mount comes standard with 1/2" NPT Adapter<br> |
|  | SLMBP-PNP-012-024GY | Gray       | 12-24VAC/DC |  |
|  | SLMBP-120-240GY     | Gray       | 120-240VAC  |  |
| <br>Twin Wall Mount   | SLMBT-012-024GY     | Gray       | 12-24VAC/DC |   |
|  | SLMBT-PNP-012-024GY | Gray       | 12-24VAC/DC |  |
|  | SLMBT-120-240GY     | Gray       | 120-240VAC  |  |
| <br>2-Stack Dock Base<br><br>3-Stack Dock Base | SLMB2-024GY         | Gray       | 24VAC/DC    |   |
|  | SLMB2-120-240GY     | Gray       | 120-240VAC  |  |
|  | SLMB3-024GY         | Gray       | 24VAC/DC    |  |
|  | SLMB3-120-240GY     | Gray       | 120-240VAC  |  |

Note: Dock bases allow one function per position and include visors.



www.delga.com

delgasa@delga.com

+5411 4298-0184