



Model SLM800 shown with mounting base options (ordered separately)

► Model SLM800

StreamLine® Modular High-Output Electronic Sounder

Model SLM800 is a high-output multifunctional electronic sounder developed with a multiple input technology that is capable of producing two different tones (pre-alarm, alarm) controllable via independent electric contacts.

Model SLM800 offers a high acoustic performance through 2 channels offering 64 tones, 32 tones per input selectable via DIP switch.

Model SLM800 body material is a self-extinguishing polycarbonate material with high impact and UV resistance suitable for outdoor applications.

FEATURES

- Compatible with 12-24VAC/DC or 120-240VAC*
 - PLC compatible with PNP or NPN connections*
 - Produces two tones
 - Choice of 64 selectable tones
 - Adjustable volume between 55 dBA to 105 dBA @ 10' (65-115 dBA @ 1m)
 - Five mounting base options
 - Type 3R, IP65 enclosure
 - CE Certified
 - UL and cUL listed
- * Voltage and PLC connections are dependent on selected base.

MODEL	VOLTAGE	DECIBELS MIN. - MAX.		MAXIMUM OPERATING CURRENT (mA)			
		10'	1M	12VAC/DC	24VAC/DC	120VAC	240VAC
SLM800 *	12-24VAC/DC	55-105	65-115	240	280	–	–
	120-240VAC	55-101	65-111	–	–	60	35

*For body color, indicate GY for Gray or R for Red.


Weight (unit(s) + base = total weight)

SLM800	VOLTAGE	SHALLOW BASE	DEEP BASE	WALL MOUNT	PIPE MOUNT	TWIN WALL MOUNT
19.05 oz 0.54 kg	12-24VAC/DC	2.12 oz 0.06 kg	4.23 oz 0.12 kg	6.70 oz 0.19 kg	5.29 oz 0.15 kg	9.17 oz 0.26 kg
	120-240 VAC	–	6.0 oz 0.17 kg	8.47 oz 0.24 kg	6.70 oz 0.19 kg	12.35 oz 0.35 kg

StreamLine® Modular High-Output Electronic Sounder (SLM800)

SPECIFICATIONS











Operating Temperature: -22°F to 122°F -30°C to 50°C



HOW TO ORDER

- Specify model number:
SLM800GY - Gray body
SLM800R - Red body
- Specify required mounting base (see chart)
- Optional dome guard
For shallow mounting base (SLMDG1)
For deep mounting base (SLMDG2)
- Accessories for Twin and Wall Mount Bases
Cable Gland, M20, Gray, 2 Pack (K77700416)
Cable Gland, M20, Red, 2 Pack (K77700416-01)
- Accessories for Pipe Mount Base
1" NPT Adapter (SLMNPT1)
1/2" NPT Adapter (SLMNPT2)

MOUNTING BASE OPTIONS

	Model Number	Base Color	Voltage	
 Shallow Base	SLMBS-012-024GY	Gray	12-24VAC/DC	
	SLMBS-012-024R	Red	12-24VAC/DC	
 Deep Base	SLMBD-012-024GY	Gray	12-24VAC/DC	
	SLMBD-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBD-012-024R	Red	12-24VAC/DC	
	SLMBD-120-240GY	Gray	120-240VAC	
 Wall Mount	SLMBW-012-024GY	Gray	12-24VAC/DC	
	SLMBW-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBW-120-240GY	Gray	120-240VAC	
 Pipe Mount	SLMBP-012-024GY	Gray	12-24VAC/DC	Pipe Mount comes standard with 1/2" NPT Adapter 
	SLMBP-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBP-120-240GY	Gray	120-240VAC	
 Twin Wall Mount	SLMBT-012-024GY	Gray	12-24VAC/DC	
	SLMBT-PNP-012-024GY	Gray	12-24VAC/DC	
	SLMBT-120-240GY	Gray	120-240VAC	



www.delga.com | delgasa@delga.com | +5411 4298-0184